

ULTRA DECK

ULTRADECK LUXE SERIES

Care & Maintenance Guide



No oiling, staining
or sealing



Tested & built
to last longer



Up to 25-year
warranty

ultradeck.com.au

OVERVIEW

The Ultradeck Luxe Series is not a self-cleaning product. It will need regular cleaning, particularly in undercover or alfresco areas.

Cleaning needs for your Ultradeck Luxe Series will depend on how the product is used and its exposure to the elements. Stains can occur if cleaning is not performed regularly.

While the Ultrashield coating of the Ultradeck Luxe Series is resistant to most stains, it's advisable to remove foreign substances promptly to minimize the risk of staining or discoloration.

This guide provides essential principles to help you preserve the natural beauty of your Ultradeck Luxe Series Series.

SURFACE PROTECTION

To prevent scratching or marking your Ultradeck, it is recommended to use surface protection on furniture and other objects.

WEATHERING

Ultradeck is a color-fast, UV-stabilized product designed to maintain its color over time. Like any outdoor material, a slight color shift may occur upon initial UV exposure. This is a natural effect and not a product defect.

GENERAL CLEAN

A General Clean is essential right after installation to remove any surface debris from transport and setup, and should also be done periodically as needed:

1. Mop the deck with warm water and dishwashing liquid using a soft mop.
2. Rinse the deck thoroughly with a low-pressure garden hose.

We recommend performing a General Clean at least once a year to minimize potential surface oxidation.

****Note:**** Care must be taken when using a high-pressure washer, as it can cause permanent damage to your deck.

Maintain a minimum separation of 30cm between the nozzle outlet and decking surface.

STUBBORN STAINS

If a General Clean doesn't remove stubborn stains from your deck, a stain remover may be necessary. We recommend using an aerosol car or engine degreaser to tackle oil-based stains. Simply spray the affected area and gently scrub with a microfiber cloth.

Be sure to follow up with a General Clean to wash away any remaining degreaser.

MOULD

Mold growth is often due to constant moisture and shade in the surrounding environment. A dirty deck can also encourage mold to develop and spread.

If mold appears on your Ultradeck Luxe Series, we recommend using 30 Seconds Mould Off for removal.

For recurring mold, more frequent cleaning is advised.

STATIC ELECTRICITY

In rare cases, co-extruded composite decking may build up static electricity.

This can be managed with an anti-static spray if needed.

Typically, static build-up will decrease as the boards naturally wear over time.

SLIP RATING

Ultradeck decking boards come with a certified anti-slip rating in compliance with AS4586:2013.

Over time, factors such as foot traffic, environmental conditions, and other external influences may cause surface wear.

It is the owner's responsibility to periodically test the boards to ensure they continue to meet anti-slip rating requirements.

